



**The on-board models**  
**Marine range from 1000 to 5200 kg/24 h –**  
**Fresh and sea water**



Geneglance S.A.S.  
9 rue des Orfèvres  
44840 Les Sorinières - FRANCE  
T : +33(0) 2 51 19 10 51 – F : +33(0)2 40 05 73 81  
[www.geneglance.com](http://www.geneglance.com) - [contact@geneglance.com](mailto:contact@geneglance.com)



Generator alone to be connected to a refrigeration plant or dedicated unit.

Generator alone				
Water	Model	Production Kg /24h	Dimensions LxlxH (cm)	Weight (KG)
Fresh water	F30 M TRI	1 000 kg	75x50x180	90
	F100 M TRI	2 500 kg	90x70x145	220
Sea water	F100 SW TRI	2 500 kg	90x70x145	220

- Sea water temperature (Condensor) : +20 °C
- Water temperature : +20 °C
- Refrigerant : R404A
- Option 24V available
- Liquid inlet : thermostat express valve

For other working conditions, please consult us.



Generator F100M

### Plug and play flake ice production

Pack											
Water	Model	Production Kg /24h	Charge (Kg)	Ice Thickness (mm)	Evaporating Temperature (°C)	Dimensions Longxlargxh (cm)	Weight (Kg)	Sea water (m/h) (condenseur)	Voltage (v-hz)	Installed Power (kVa)	Consumed energy (kW/h)
Fresh water	Pack F30M	1 000 kg	12 kg	1,9	-25	120 x 100 x 100	420	3	400/3/50	6	74
	Pack F100M	2 500 kg	35 kg	2	-28	130 x 130 x 130	700	6	400/3/50	12	65
	Pack F100 2M	5 000 Kg	50 kg	2	-28	163 x 163 x 130	1 200	12	400/3/50	23	59
Sea water	Pack F100 SW	2 600 kg	35 kg	2,1	-35	130 x 130 x 130	700	8	400/3/50	16,5	67
	Pack F100 2SW	5 200 kg	50 Kg	2,1	-35	163 x 163 x 130	1 200	16	400/3/50	33	71

- Sea water temperature (Condensor) : +20 °C
- Water temperature : +20 °C
- Refrigerant : R404A
- Liquid inlet : thermostat express valve
- Refrigerating unit : Compressor type Open, Direct Starting, Belt driving

\*For other working conditions, please consult us.



Pack F100SW